


V: 2021.12 SIM8200G

SIMCom 5G Sub-6G Module



Product Description

The SIM8200G is Multi-Band 5G NR/LTE-FDD/LTE-TDD/HSPA+ module which supports R15 5G NSA/SA up to 4Gbps data transfer.

It has strong extension capability with abundant interfaces including PCIe, USB3.1, GPIO etc. The module provides much flexibility and ease of integration for customer's applications.

SIM8200G adopts LGA form factor and the AT commands are compatible with SIM8300 series modules. This also minimizes the investments of customers and enables a short time-to-market.

It is designed for applications that need high throughput data communication in a variety of radio propagation conditions. Due to the unique combination of performance, security and flexibility, this module is ideally suited for many applications.

Key Benefits

- LGA form factor with abundant interfaces
- High throughput data communication
- The AT commands of SIM8200G are compatible with SIM8300 series modules



Product		SIM8200G V1.02	SIM8200G V4.01	SIM8200G V3.02
Form Factor		LGA	LGA	LGA
Dimensions(mm)		41.0*43.6*2.8	41.0*43.6*2.8	41.0*43.6*2.8
Freque ncy Bands	5G-SA	n1,n2,n3,n5,n7,n8,n12,n20,n28,n38,n40,n41,n48,n66,n71,n77,n78,n79		n1,n2, <mark>n3,n5</mark> ,n7,n8 <mark>,n12,n20,n25,n28</mark> ,n38, n40,n41,n48,n66,n71,n77,n78,n79
	5G-NSA	n41,n77,n78,n79	n41,n77,n78,n79	n1,n2*,n3*,n5*,n7*,n28,n41,n77,n78,n79
	LTE-FDD	B1/B2/B3/B4/B5/B7/B8/B12/B13/B1 4/B17/B18/B19/B20/B25/B26/B28/B 29/B30/B32/B66/B71	B1/B3/B5/B7*/B8/B20/B28	B1/B2/B3/B4/B5/B7/B8/B12/B13/B14/B17/ B18/B19/B20/B25/B26/B28/B29/B30/B32/ B46/B66/B71
	LTE-TDD	B34/B38/B39/B40/B41/B42/B43/B4 8	B34/B38/B39/B40/B41/B42/B43/B48	B34/B38/B39/B40/B41/B42/B43/B48
	WCDMA	B1/B2/B3/B4/B5/B8	B1/B3/B5/B8	B1/B2/B3/B4/B5/B8
Ant		8	4	5
GNSS		•	•	•
Temper	ature	-30°C ~ +70°C	-30°C ~ +70°C	-30°C ~ +70°C
Electric	al Features	5		
Supply	Voltage(V)	3.3 ~ 4.4		
Data Tra	ansfer			
5G		2.4Gbps(DL)/1Gbps(UL)	2.4Gbps(DL)/1Gbps(UL)	2.4Gbps(DL)/1Gbps(UL)
LTE		1Gbps(DL)/200Mbps(UL)	1Gbps(DL)/200Mbps(UL)	1Gbps(DL)/200Mbps(UL)
HSPA+		42Mbps (DL)/5.75Mbps(UL)	42Mbps (DL)/5.75Mbps(UL)	42Mbps (DL)/5.75Mbps(UL)
Softwar	e Features			
Protocol T		TCP/IP/IPV4/IPV6/Multi-PDP/FTPS/HTTP/HTTPS/MQTTS/DNS/SSL3.0		
TLS		•	•	•
File System		•	•	•
FOTA		•	•	•
Android RIL		Android 6/7/8/9	Android 6/7/8/9	Android 6/7/8/9
USB Dri	JSB Driver Microsoft Windows Win7/Win8/Win10/Linux/Android			
MBIM		Win8/Win10	Win8/Win10	Win8/Win10
NDIS		Linux/Win7/Win8/Win10	Linux/Win7/Win8/Win10	Linux/Win7/Win8/Win10
Firmwa	re Upgrade	USB	USB	USB
Interfac				
SIM Car	rd	1.8V/2.95V	1.8V/2.95V	1.8V/2.95V
USB		•	•	•
PCM		•	•	•
I2C		•	•	•
Diversity Receive		•	•	•
Certifica				
Regulat		CCC/CTA/SRRC/RoHS/REACH/JA TE/TELEC/CE(RED)/FCC*	CE*/FCC*	CE*/FCC*

^{•:} support o: optional *: means under developing/on-going/planning